

ASPHALT > MIXING

## MARSHALL MIXER

Code : A050



- Used to mix the samples with bituminous materials. The mixer provides uniform and quick mixing process.
- The beaters in the mixer rotates in both planetary and spindle ways to provide the best and the most efficient mixing state.
- Equipped with a stainless steel bowl and beater.

### **STANDARDS**

EN 12947-3 • BS 548-107

### **TECHNICAL SPECIFICATIONS**

#### **5 Liters Model:**

- Capacity: 5 lt (Ø 200 x 160 mm)
- Spindle Speed: 420 rpm
- Planetary Speed: 130 rpm
- Supplied with:
  - Stainless steel bowl
  - Stainless steel beater
  - Equipped with Safety Switch
- 220 - 240 V / 50 Hz

**10 Liters Model:**

- Capacity: 10 lt
- Spindle Speed: 420 rpm
- Planetary Speed: 130 rpm
- Supplied with:
  - Stainless steel bowl
  - Stainless steel beater
  - Equipped with Safety Switch
- 220 - 240 V / 50 Hz

**20 Liters Model:**

- Capacity: 20 lt
- Spindle Speed: 75 rpm
- Planetary Speed: 45 rpm
- Supplied with:
  - 30 lt stainless steel bowl
  - stainless steel beater
  - Equipped with Digital Timer and Digital Thermometer
- 220 - 240 V / 50 Hz

## **ORDERING INFORMATION**

Item	Code
MARSHALL MIXER w/ HEATER - 5 lt	A050X05XU
MARSHALL MIXER w/ HEATER - 10 lt	A050X10XU
MARSHALL MIXER w/ HEATER - 20 lt	A050X20XU
BEATER for MARSHALL MIXER (5 lt)	A050P001H
BOWL for MARSHALL MIXER (5 lt)	A050P002H
BEATER for MARSHALL MIXER (10 lt)	A050P003H
BOWL for MARSHALL MIXER (10 lt)	A050P004H
BEATER for MARSHALL MIXER (20 lt)	A050P005H
BOWL for MARSHALL MIXER (20 lt)	A050P006H

## **OTHER PHOTOS**



